

TS
ステンレス
RoHS適合



線径: $\phi 0.35\sim\phi 3.20$ の
116種類

*準標準品とは、在庫を持たない受注対応製品です。
(納期に関しては御相談下さい。)

*右記の価格は1ヶ当り消費税抜き価格です。

TP
硬鋼線
RoHS適合




線径: $\phi 0.35\sim\phi 3.20$ の
116種類

*準標準品とは、在庫を持たない受注対応製品です。
(納期に関しては御相談下さい。)

*右記の価格は1ヶ当り消費税抜き価格です。

種類	材質	線径	外径	自由長	単価(円)		
					1個~	5個~	10個~
T S	0.35	2.9	500	1100	880	725	
		3.2	"	1150	920	755	
		3.5	"	1160	925	760	
		4.0	"	1175	940	775	
		4.5	"	1185	945	775	
		5.0	"	1195	955	785	
		3.5	500	1170	935	770	
T S	0.40	4.0	"	1180	940	775	
		4.5	"	1190	950	780	
		5.0	"	1205	960	790	
		5.5	"	1220	975	800	
		6.0	"	1230	980	805	
		3.5	500	1170	935	770	
		4.0	"	1180	940	775	
T S	0.45	4.5	"	1190	950	780	
		5.0	"	1205	960	790	
		5.5	"	1215	970	800	
		6.0	"	1230	980	805	
		3.5	500	1170	935	770	
		4.0	"	1180	940	775	
		4.5	"	1190	950	780	
T S	0.50	5.0	"	1205	960	790	
		5.5	"	1215	970	800	
		6.0	"	1230	980	805	
		3.5	500	1170	935	770	
		4.0	"	1180	940	775	
		4.5	"	1190	950	780	
		5.0	"	1205	960	790	
T S	0.55	5.5	"	1215	970	800	
		6.0	"	1230	980	805	
		6.5	"	1240	990	815	
		7.0	"	1255	1000	825	
		7.5	"	1265	1010	830	
		8.0	"	1275	1025	845	
		8.5	"	1285	1040	855	
T S	0.60	9.0	"	1295	1055	870	
		9.5	"	1300	1060	880	
		10.0	"	1310	1075	890	
		10.5	"	1320	1085	895	
		11.0	"	1330	1090	905	
		11.5	"	1340	1095	910	
		12.0	"	1350	1095	915	
T S	0.65	12.5	"	1360	1100	920	
		13.0	"	1370	1105	925	
		13.5	"	1380	1110	930	
		14.0	"	1390	1115	935	
		14.5	"	1400	1120	940	
		15.0	"	1410	1125	945	
		15.5	"	1420	1130	950	
T S	0.70	16.0	"	1430	1135	955	
		16.5	"	1440	1140	960	
		17.0	"	1450	1145	965	
		17.5	"	1460	1150	970	
		18.0	"	1470	1155	975	
		18.5	"	1480	1160	980	
		19.0	"	1490	1165	985	
T S	0.80	19.5	"	1500	1170	990	
		20.0	"	1510	1175	995	
		20.5	"	1520	1180	1000	
		21.0	"	1530	1185	1005	
		21.5	"	1540	1190	1010	
		22.0	"	1550	1195	1015	
		22.5	"	1560	1200	1020	
T S	0.90	23.0	"	1570	1205	1025	
		23.5	"	1580	1210	1030	
		24.0	"	1590	1215	1035	
		24.5	"	1600	1220	1040	
		25.0	"	1610	1225	1045	
		25.5	"	1620	1230	1050	
		26.0	"	1630	1235	1055	
T S	1.00	26.5	"	1640	1240	1060	
		27.0	"	1650	1245	1065	
		27.5	"	1660	1250	1070	
		28.0	"	1670	1255	1075	
		28.5	"	1680	1260	1080	
		29.0	"	1690	1265	1085	
		29.5	"	1700	1270	1090	
T S	1.20	30.0	"	1710	1275	1095	
		30.5	"	1720	1280	1100	
		31.0	"	1730	1285	1105	
		31.5	"	1740	1290	1110	
		32.0	"	1750	1295	1115	
		32.5	"	1760	1300	1120	
		33.0	"	1770	1305	1125	
T P	0.35	33.5	"	1780	1310	1130	
		34.0	"	1790	1315	1135	
		34.5	"	1800	1320	1140	
		35.0	"	1810	1325	1145	
		35.5	"	1820	1330	1150	
		36.0	"	1830	1335	1155	
		36.5	"	1840	1340	1160	
T P	0.40	37.0	"	1850	1345	1165	
		37.5	"	1860	1350	1170	
		38.0	"	1870	1355	1175	
		38.5	"	1880	1360	1180	
		39.0	"	1890	1365	1185	
		39.5	"	1900	1370	1190	
		40.0	"	1910	1375	1195	
T P	0.45	40.5	"	1920	1380	1200	
		41.0	"	1930	1385	1205	
		41.5	"	1940	1390	1210	
		42.0	"	1950	1395	1215	
		42.5	"	1960	1400	1220	
		43.0	"	1970	1405	1225	
		43.5	"	1980	1410	1230	
T P	0.50	44.0	"	1990	1415	1235	
		44.5	"	2000	1420	1240	
		45.0	"	2010	1425	1245	
		45.5	"	2020	1430	1250	
		46.0	"	2030	1435	1255	
		46.5	"	2040	1440	1260	
		47.0	"	2050	1445	1265	
T P	0.55	47.5	"	2060	1450	1270	
		48.0	"	2070	1455	1275	
		48.5	"	2080	1460	1280	
		49.0	"	2090	1465	1285	
		49.5	"	2100	1470	1290	
		50.0	"	2110	1475	1295	
		50.5	"	2120	1480	1300	
T P	0.60	51.0	"	2130	1485	1305	
		51.5	"	2140	1490	1310	
		52.0	"	2150	1495	1315	
		52.5	"	2160	1500	1320	
		53.0	"	2170	1505	1325	
		53.5	"	2180	1510	1330	
		54.0	"	2190	1515	1335	
T P	0.65	54.5	"	2200	1520	1340	
		55.0	"	2210	1525	1345	
		55.5	"	2220	1530	1350	
		56.0	"	2230	1535	1355	
		56.5	"	2240	1540	1360	
		57.0	"	2250	1545	1365	
		57.5	"	2260	1550	1370	
T P	0.70	58.0	"	2270	1555	1375	
		58.5	"	2280	1560	1380	
		59.0	"	2290	1565	1385	
		59.5	"	2300	1570	1390	
		60.0	"	2310	1575	1395	
		60.5	"	2320	1580	1400	
		61.0	"	2330	1585	1405	
T P	0.75	61.5	"	2340	1590	1410	
		62.0	"	2350	1595	1415	
		62.5	"	2360	1600	1420	
		63.0	"	2370	1605	1425	
		63.5	"	2380	1610	1430	
		64.0	"	2390	1615	1435	
		64.5	"	2400	1620	1440	
T P	0.80	65.0	"	2410	1625	1445	
		65.5	"	2420	1630	1450	

TS
ステンレス
RoHS適合



線径: $\phi 0.35 \sim \phi 3.20$ の
116種類


*準標準品とは、在庫を持たない受注対応製品です。
(納期に関しては御相談下さい。)

*右記の価格は1ヶ当り消費税抜き価格です。

種類	材質	線径	外径	自由長	単価(円)		
					1個~	5個~	10個~
T S	1.40	11.0	500	1380	1130	930	
		12.0	"	1410	1155	950	
		13.0	"	1430	1170	965	
		14.0	"	1440	1180	970	
		15.0	"	1470	1205	990	
		16.0	"	1500	1230	1010	
		17.0	"	1530	1255	1030	
T S	1.60	12.0	500	1465	1200	990	
		13.0	"	1495	1225	1010	
		14.0	"	1525	1250	1030	
		15.0	"	1555	1275	1050	
		16.0	"	1585	1295	1065	
		17.0	"	1615	1320	1085	
		18.0	"	1645	1345	1105	
T S	1.80	14.0	500	1590	1300	1070	
		15.0	"	1625	1330	1095	
		16.0	"	1655	1355	1115	
		17.0	"	1685	1380	1135	
		18.0	"	1715	1405	1155	
		20.0	"	1745	1435	1180	
		22.0	"	1775	1465	1200	
T S	2.00	14.0	500	1715	1455	1270	
		16.0	"	1745	1480	1295	
		18.0	"	1775	1505	1315	
		20.0	"	1810	1535	1340	
		22.0	"	1840	1560	1365	
		24.0	"	1870	1585	1385	
		26.0	"	1900	1610	1405	
T S	2.30	16.0	500	1725	1465	1280	
		18.0	"	1755	1500	1330	
		20.0	"	1785	1525	1350	
		22.0	"	1815	1550	1370	
		24.0	"	1845	1575	1395	
		26.0	"	1875	1605	1425	
		28.0	"	1905	1635	1455	
T S	2.60	18.0	500	1770	1500	1310	
		20.0	"	1800	1525	1330	
		22.0	"	1830	1555	1360	
		24.0	"	1860	1585	1395	
		26.0	"	1890	1615	1425	
		28.0	"	1920	1645	1455	
		30.0	"	1950	1675	1485	

種類	材質	線径	外径	自由長	単価(円)		
					1個~	5個~	10個~
T S	2.90	20.0	500	1915	1625	1420	
		22.0	"	1945	1735	1515	
		24.0	"	1975	1845	1610	
		26.0	"	2005	1890	1650	
		28.0	"	2035	1920	1750	
		30.0	"	2065	1955	1755	
		32.0	"	2095	1980	1760	

TP
硬鋼線
RoHS適合



線径: $\phi 0.35 \sim \phi 3.20$ の
116種類

*準標準品とは、在庫を持たない受注対応製品です。
(納期に関しては御相談下さい。)

*右記の価格は1ヶ当り消費税抜き価格です。

種類	材質	線径	外径	自由長	単価(円)		
					1個~	5個~	10個~
T P	1.40	11.0	500	1150	940	775	
		12.0	"	1175	960	790	
		13.0	"	1200	980	805	
		14.0	"	1200	980	805	
		15.0	"	1225	1000	825	
		16.0	"	1250	1025	845	
		17.0	"	1275	1050	865	
T P	1.60	12.0	500	1200	980	805	
		13.0	"	1225	1000	825	
		14.0	"	1250	1025	845	
		15.0	"	1275	1045	860	
		16.0	"	1300	1065	875	
		17.0	"	1325	1085	895	
		18.0	"	1350	1105	910	
T P	1.80	14.0	500	1275	1045	860	
		15.0	"	1300	1065	875	
		16.0	"	1325	1085	895	
		17.0	"	1350	1105	910	
		18.0	"	1375	1125	925	
		20.0	"	1400	1145	940	
		22.0	"	1425	1165	955	
T P	2.00	14.0	500	1350	1145	1000	
		16.0	"	1375	1165	1015	
		18.0	"	1400	1190	1040	
		20.0	"	1425	1210	1055	
		22.0	"	1450	1230	1075	
		24.0	"	1475	1250	1090	
		26.0	"	1500	1275	1115	
T P	2.30	16.0	500	1350	1145	1000	
		18.0	"	1400	1190	1040	
		20.0	"	1450	1230	1075	
		22.0	"	1500	1275	1115	
		24.0	"	1550	1315	1150	
		26.0	"	1600	1350	1190	
		28.0	"	1650	1400	1225	

種類	材質	線径	外径	自由長	単価(円)		
					1個~	5個~	10個~
T P	2.90	20.0	500	1450	1230	1075	
		22.0	"	1500	1315	1150	
		24.0	"	1650	1400	1225	
		26.0	"	1750	1485	1295	
		28.0	"	1850	1570	1370	
		30.0	"	1950	1655	1445	
		32.0	"	2100	1785	1560	

ご注文時のFAX申し込み用紙への記入例

注文品Aに種類・材質・線径・外径・自由長を記入して下さい。

密着コイルばねのTS、線径Φ1.40、外径11.0、自由長500mmの場合、型式はTS 1.4-11-500となります。

<記入例>

種類	材質	線径	コイル外径	自由長	方向	数量
C T	S P	1.4 0	11.0	500 0 0		1