

# DWT Fmax (許容たわみ量) = L × 40% (L × 35%)

■数量別価格値引率 (1円未満切捨て)

数量 値引率	1~9	10~19	20~99	100~500
	表示価格	5%	10%	15%

外径 D	自由長 L	線径 d	密着長 mm(約)	F max	荷重 N(kgf)	code No.	単価 1~9個
3	* 5	0.30	1.73	2	2.9 (0.3)	DWT 3-5	54
	* 10	0.40	5.4	4	5.9 (0.6)	10	
	* 15	0.45	9.5	6	8.8 (0.9)	15	
	* 20	0.45	9.5	8	11.8 (1.2)	20	
	* 25	0.50	16.2	10	14.7 (1.5)	25	
4	* 5	0.40	2.7	2	2.9 (0.3)	DWT 4-5	59
	* 10	0.40	2.7	4	5.9 (0.6)	10	
	* 15	0.50	6.5	6	8.8 (0.9)	15	
	20	0.55	9.6	8	11.8 (1.2)	20	
	25	0.55	9.6	10	14.7 (1.5)	25	63
	30	0.60	15.0	12	17.7 (1.8)	30	
	35	0.60	15.0	14	20.6 (2.1)	35	
	40	0.65	22.1	16	23.5 (2.4)	40	
5	* 5	0.45	2.4	2	3.9 (0.4)	DWT 5-5	62
	* 10	0.50	3.3	4	7.8 (0.8)	10	
	15	0.60	6.3	6	11.8 (1.2)	15	
	20	0.60	6.3	8	15.7 (1.6)	20	
	25	0.70	12.6	10	19.6 (2.0)	25	
	30	0.70	12.6	12	23.5 (2.4)	30	66
	35	0.75	17.3	14	27.5 (2.8)	35	
	40	0.75	17.3	14.0	27.5 (2.8)	40	
	45	0.80	24.9	15.7	30.4 (3.1)	45	68
	50	0.80	24.9	17.5	34.3 (3.5)	50	
	55	0.85	32.3	19.2	37.3 (3.8)	55	
	60	0.85	34.5	21.0	41.2 (4.2)	60	
	65	0.85	34.5	22.7	44.1 (4.5)	65	
70	0.90	44.6	24.5	48.1 (4.9)	70		
6	* 5	0.50	2.4	2	3.9 (0.4)	DWT 6-5	63
	10	0.60	4.3	4	7.8 (0.8)	10	
	15	0.60	4.3	6	11.8 (1.2)	15	
	20	0.70	7.7	8	15.7 (1.6)	20	
	25	0.70	7.7	10	19.6 (2.0)	25	
	30	0.80	14.0	12	23.5 (2.4)	30	68
	35	0.80	14.0	14	27.5 (2.8)	35	
	40	0.85	18.7	16	31.4 (3.2)	40	
	45	0.85	18.7	18	35.3 (3.6)	45	72
	50	0.90	24.8	20	39.2 (4.0)	50	
	55	0.90	24.8	19.2	37.3 (3.8)	55	
	60	0.90	24.8	21.0	41.2 (4.2)	60	
	65	0.90	26.1	22.7	44.1 (4.5)	65	
70	1.00	43.0	24.5	48.1 (4.9)	70		
80	1.00	39.7	28.0	54.9 (5.6)	80		
8	10	0.70	4.0	4	7.8 (0.8)	DWT 8-10	72
	15	0.80	6.8	6	11.8 (1.2)	15	
	20	0.80	6.8	8	15.7 (1.6)	20	
	25	0.80	6.8	10	19.6 (2.0)	25	
	30	0.90	10.8	12	23.5 (2.4)	30	
	35	0.90	10.8	14	27.5 (2.8)	35	77
	40	1.00	17.5	16	31.4 (3.2)	40	
	45	1.00	17.5	18	35.3 (3.6)	45	
	50	1.00	17.5	20	39.2 (4.0)	50	81
	55	1.10	27.5	22	43.1 (4.4)	55	
	60	1.10	27.5	24	47.1 (4.8)	60	
	65	1.10	27.5	26	51.0 (5.2)	65	
	70	1.10	27.5	28	54.9 (5.6)	70	
80	1.20	42.0	32	62.8 (6.4)	80		
10	10	0.85	5.0	4	7.8 (0.8)	DWT 10-10	81
	15	0.90	6.3	6	11.8 (1.2)	15	
	20	0.90	6.3	8	15.7 (1.6)	20	
	25	1.00	10.0	10	19.6 (2.0)	25	
	30	1.00	10.0	12	23.5 (2.4)	30	
	35	1.00	10.0	14	27.5 (2.8)	35	86
	40	1.00	10.0	16	31.4 (3.2)	40	
	45	1.10	14.3	18	35.3 (3.6)	45	
	50	1.10	14.3	20	39.2 (4.0)	50	86
	55	1.20	21.6	22	43.1 (4.4)	55	
	60	1.20	21.6	24	47.1 (4.8)	60	
	65	1.20	21.6	26	51.0 (5.2)	65	
	70	1.30	32.5	28	54.9 (5.6)	70	
80	1.30	32.5	32	62.8 (6.4)	80		

外径 D	自由長 L	線径 d	密着長 mm(約)	F max	荷重 N(kgf)	code No.	単価 1~9個
13	15	1.00	6.0	6	11.8 (1.2)	DWT 13-15	86
	20	1.10	7.5	8	15.7 (1.6)	20	
	25	1.10	7.5	10	19.6 (2.0)	25	
	30	1.20	11.1	12	23.5 (2.4)	30	
	35	1.20	11.1	14	27.5 (2.8)	35	
	40	1.20	11.1	16	31.4 (3.2)	40	
	45	1.20	11.1	18	35.3 (3.6)	45	
	50	1.30	15.6	20	39.2 (4.0)	50	
	55	1.30	15.6	22	43.1 (4.4)	55	
	60	1.30	15.6	24	47.1 (4.8)	60	
16	15	1.20	7.5	6	11.8 (1.2)	DWT 16-15	108
	20	1.30	8.5	8	15.7 (1.6)	20	
	25	1.40	12.6	10	19.6 (2.0)	25	
	30	1.40	12.6	12	23.5 (2.4)	30	
	35	1.40	12.6	14	27.5 (2.8)	35	
	40	1.40	12.6	16	31.4 (3.2)	40	
	45	1.60	22.4	18	35.3 (3.6)	45	
	50	1.60	22.4	20	39.2 (4.0)	50	
	55	1.60	22.4	22	43.1 (4.4)	55	
	60	1.70	28.9	24	47.1 (4.8)	60	
18	20	1.60	10.8	8	31.4 (3.2)	DWT 18-20	126
	25	1.70	13.6	10	39.2 (4.0)	25	
	30	1.70	13.6	12	47.1 (4.8)	30	
	35	1.70	13.6	14	54.9 (5.6)	35	
	40	1.80	16.7	16	62.8 (6.4)	40	
	45	1.90	20.5	18	70.6 (7.2)	45	
	50	1.90	20.5	20	78.5 (8.0)	50	
	55	2.00	26.0	22	86.3 (8.8)	55	
	60	2.00	26.0	24	94.1 (9.6)	60	
	65	2.00	26.0	26	102.0 (10.4)	65	
22	20	1.80	11.3	8	31.4 (3.2)	DWT 22-20	135
	25	1.80	11.3	10	39.2 (4.0)	25	
	30	1.90	13.3	12	47.1 (4.8)	30	
	35	1.90	13.3	14	54.9 (5.6)	35	
	40	2.00	16.0	16	62.8 (6.4)	40	
	45	2.10	19.5	18	70.6 (7.2)	45	
	50	2.10	19.5	20	78.5 (8.0)	50	
	55	2.30	28.2	22	86.3 (8.8)	55	
	60	2.30	28.2	24	94.1 (9.6)	60	
	65	2.30	28.2	26	102.0 (10.4)	65	
27	30	2.10	13.2	12	47.1 (4.8)	DWT 27-30	153
	35	2.30	17.9	14	54.9 (5.6)	35	
	40	2.30	17.9	16	62.8 (6.4)	40	
	45	2.40	20.4	18	70.6 (7.2)	45	
	50	2.60	28.6	20	78.5 (8.0)	50	
	55	2.60	28.6	22	86.3 (8.8)	55	
	60	2.60	28.6	24	94.1 (9.6)	60	
	65	2.60	28.6	26	102.0 (10.4)	65	
	70	2.80	39.2	28	109.8 (11.2)	70	
	80	2.80	39.2	32	125.5 (12.8)	80	

外径 D	3	4	5	6	8	10	13	16	18	22	27
バネ定数	1.5N/mm (0.15Kgf/mm)			2.0N/mm (0.2Kgf/mm)				3.9N/mm (0.4Kgf/mm)			

※荷重は参考値となります。

バネ定数	±10%	
外径 D	φ10以下	0mm -0.5mm
	φ12以上	0mm -0.8mm
自由長 L	50以下	±1.5mm
	55以上	±2.0mm

材質：SWPB  
DWTタイプは両端研削です。(\*印は両端無研削です。)  
密着長は参考値です。ロットによってバラツキがあります。  
使用回数：100万回  
荷重(kgf) = 荷重(N) × 0.101972