

DWY Fmax (許容たわみ量) = L × 75%

■数量別価格値引率 (1円未満切捨て)

数量	1~9	10~19	20~99	100~500
値引率	表示価格	5%	10%	15%

外径 D	自由長 L	線径 d	密着長 mm (約)	F max	荷重 N(kgf)	code No.	単価 1~9個	
3	10	0.20	2.2	7.5	0.78 (0.08)	DWY 3-10	59	
	15	0.23	4.0	11.2	1.08 (0.11)	15		
	20	0.23	4.0	15.0	1.47 (0.15)	20		
	25	0.25	5.9	18.7	1.86 (0.19)	25		
	30	0.26	7.1	22.5	2.26 (0.23)	30		
4	5	0.20	1.1	3.8	0.39 (0.04)	DWY 4-5	63	
	10	0.23	1.9	7.5	0.78 (0.08)	10		
	15	0.23	1.9	11.2	1.08 (0.11)	15		
	20	0.25	2.7	15.0	1.47 (0.15)	20		
	25	0.29	5.0	18.7	1.86 (0.19)	25		
	30	0.29	5.0	22.5	2.26 (0.23)	30		
	35	0.32	8.1	26.2	2.55 (0.26)	35		
5	10	0.25	1.7	7.5	0.78 (0.08)	DWY 5-10	66	
	15	0.25	1.7	11.2	1.08 (0.11)	15		
	20	0.30	3.2	15.0	1.47 (0.15)	20		
	25	0.30	3.2	18.7	1.86 (0.19)	25		
	30	0.35	6.3	22.5	2.26 (0.23)	30		
	35	0.35	6.3	26.2	2.55 (0.26)	35		
	40	0.35	6.7	30.0	2.94 (0.30)	40		
6	10	0.30	2.1	7.5	0.78 (0.08)	DWY 6-10	68	
	15	0.32	2.8	11.2	1.08 (0.11)	15		
	20	0.32	2.8	15.0	1.47 (0.15)	20		
	25	0.35	4.1	18.7	1.86 (0.19)	25		
	30	0.40	7.2	22.5	2.26 (0.23)	30		
	35	0.40	7.2	26.2	2.55 (0.26)	35		
	40	0.40	7.2	30.0	2.94 (0.30)	40		
	45	0.40	7.2	33.7	3.33 (0.34)	45		
	50	0.40	7.2	37.5	3.73 (0.38)	50		
	55	0.45	12.2	41.2	4.02 (0.41)	55		
8	10	0.35	2.1	7.5	0.78 (0.08)	DWY 8-10	77	
	15	0.40	3.5	11.2	1.08 (0.11)	15		
	20	0.40	3.5	15.0	1.47 (0.15)	20		
	25	0.40	3.5	18.7	1.86 (0.19)	25		
	30	0.45	5.7	22.5	2.26 (0.23)	30		
	35	0.45	5.7	26.2	2.55 (0.26)	35		
	40	0.45	5.7	30.0	2.94 (0.30)	40		
	45	0.45	5.7	33.7	3.33 (0.34)	45		
	50	0.50	9.0	37.5	3.73 (0.38)	50		
	55	0.50	9.0	41.2	4.02 (0.41)	55		
8	60	0.50	9.0	45.0	4.41 (0.45)	60	81	
	65	0.50	9.0	48.7	4.81 (0.49)	65		
	70	0.50	9.0	52.5	5.20 (0.53)	70		
	60	0.50	9.0	45.0	4.41 (0.45)	60		86
	65	0.50	9.0	48.7	4.81 (0.49)	65		

外径 D	自由長 L	線径 d	密着長 mm (約)	F max	荷重 N(kgf)	code No.	単価 1~9個
10	15	0.50	3.0	11.2	2.16 (0.22)	DWY 10-15	90
	20	0.55	4.6	15.0	2.94 (0.30)	20	
	25	0.55	4.6	18.7	3.63 (0.37)	25	
	30	0.60	6.6	22.5	4.41 (0.45)	30	
	35	0.60	6.6	26.2	5.10 (0.52)	35	
	40	0.65	9.1	30.0	5.88 (0.60)	40	
	45	0.65	9.1	33.7	6.57 (0.67)	45	
	50	0.65	9.1	37.5	7.35 (0.75)	50	
	55	0.70	12.6	41.2	8.04 (0.82)	55	
	60	0.70	12.6	45.0	8.83 (0.90)	60	
13	20	0.60	3.9	15.0	2.94 (0.30)	DWY 13-20	95
	25	0.65	5.1	18.7	3.63 (0.37)	25	
	30	0.65	5.1	22.5	4.41 (0.45)	30	
	35	0.70	6.7	26.2	5.10 (0.52)	35	
	40	0.75	8.7	30.0	5.88 (0.60)	40	
	45	0.75	8.7	33.7	6.57 (0.67)	45	
	50	0.80	11.6	37.5	7.35 (0.75)	50	
	55	0.80	11.6	41.2	8.04 (0.82)	55	
	60	0.80	11.6	45.0	8.83 (0.90)	60	
	65	0.85	15.3	48.7	9.51 (0.97)	65	
16	20	0.65	3.6	15.0	2.94 (0.30)	DWY 16-20	117
	25	0.70	4.6	18.7	3.63 (0.37)	25	
	30	0.75	5.7	22.5	4.41 (0.45)	30	
	35	0.80	7.0	26.2	5.10 (0.52)	35	
	40	0.85	9.0	30.0	5.88 (0.60)	40	
	45	0.85	9.0	33.7	6.57 (0.67)	45	
	50	0.90	11.3	37.5	7.35 (0.75)	50	
	55	0.90	11.3	41.2	8.04 (0.82)	55	
	60	0.90	11.3	45.0	8.83 (0.90)	60	
	65	0.90	11.3	48.7	9.51 (0.97)	65	
16	70	0.90	11.3	52.5	10.30 (1.05)	70	126

材質：SWPB

DWYタイプは全点両端無研削です。

密着長は参考値です。ロットによってバラツキがあります。

使用回数：100万回

荷重(kgf) = 荷重(N) × 0.101972

外径 D	3	4	5	6	8	10	13	16
バネ定数	0.1N/mm (0.01Kgf/mm)				0.2N/mm (0.02Kgf/mm)			

※荷重は参考値となります。

バネ定数	±10%	
外径 D	φ10以下	0mm -0.5mm
	φ13以上	0mm -0.8mm
自由長 L	50以下	±1.5mm
	55以上	±2.5mm